



**BCC PRODUCTS, INC.**

**BLEHM PLASTICS**

FAST CAST – EPOXIES – URETHANES – POLYESTER PASTES – TOOLING BOARDS – RELEASE AGENTS – SILICONES

## **BP 2022 WHITE EPOXY LAMINATING RESIN**

### **DESCRIPTION:**

BP 2022 is a white epoxy laminating resin which provides a laminate of exceptional dimensional stability. The resin is color indicated (green) and will turn white as the hardener is mixed into the resin. This indicator system promotes fast and efficient mixing of the resin and hardener, insuring that they are thoroughly mixed yet wasting no time overmixing. BP 2022 provides quick wet-out of fiberglass cloth with easy brushing characteristics, while keeping run-off from vertical surfaces to a minimum.

### **USE PROCEDURE:**

BP 2022 is usually used in conjunction with a surface coat such as BP 3042, BP 3044 or BP 3046. Mix the resin and hardener in the ratio of 100 parts resin to 20 parts hardener, by weight. Continue mixing until the green indicator color disappears. Apply with either a brush or squeegee taking care to avoid excess resin-rich areas. The pot-life of a 120 gram mass will be approximately 35 minutes. Laminates should be allowed to cure for at least 16 hours at 72°F before removing from the mold. Subsequent lamination on top of a cured laminate will have excellent ply-to-ply adhesion.

### **PROPERTIES:**

Mix ratio - resin/hardener:	100/20 by weight
Viscosity - mixed:	1,900 cps
Pot life - 120 grams:	35 minutes @ 72°F
Cure time:	16 hours @ 72°F - overnight
Tensile strength - laminate:	52,500 psi
Compressive strength - laminate:	41,500 psi
Hardness:	Shore D 85

### **PRECAUTIONS:**

Skin contact should be avoided. After using, clean hands with alcohol followed by soap and water. For eye contact, flush with water and consult a physician immediately. For further safety information, please see the MSDS.

2140 Earlywood Drive, P.O. Box 327, Franklin, IN 46131  
Ph (317) 736-4090 Fax (317) 736-4872  
Web: [www.bccproducts.com](http://www.bccproducts.com) & [www.blehmplastics.com](http://www.blehmplastics.com)